

Jaw Crusher Specifications

PE / PEX Series selection reference for Octal Steel



Model	Feed in opening size(mm)	Max feed size(mm)	Discharge size(mm)	Capacity (t/h)	Rotary speed of eccentric shaft(/min)	Power (kw)	Weight (t)	Overall dimension (L×W×H)(mm)
PE-150×250	150×250	125	10-40	1-3	250	250	0.8	910×650×590
PE-200×330	200×300	180	15-50	2-6	260	285	1.2	910×750×990
PE-250×350	200×350	180	18-70	3-10	260	301	1.5	1000×870×790
PE-400×680	250×400	340	40-60	16-60	275	55	2.8	1790×1090×1530
PE-600×750	500×750	425	50-100	40-110	275	55	12	1980×2080×2300
PE-800×750	600×600	630	80-140	110-320	275	90	11	2100×2200×2800
PE-900×1200	750×1060	750	95-185	220-450	200	110	110	2580×2805×2800
PE-900×1500	1000×1200	1020	180-265	300-250	250	200	32	3380×2870×3330
PE-900×1500	1200×1300	1020	180-330	400-460	200	270	55	3870×3664×8090
PE-100×1500	1200×1300	1500	220-350	480-1800	250	280	75	3790×8950×3500
PEX-250×1500	1200×1500	1702	20-40	8-25	300	33	3.8	2700×3000×2850
PEX-250×1200	2500×2000	210	25-60	13-35	330	33	5.5	1200×1580×2000
PEX-500×1500	2500×1500	210	19-52	16-52	330	37	17	2140×1690×2500
PEX-300×1500	300×11500	250	20-90	16-105	300	90	16.5	2360×2650×1505